



DIAM.	L	ES	A	Z	H	B	N	S	D	E	RB	ER	RA	R	NOTE
	+0.5 -0.5	-0.2 -0.6	+0.2 -0.2	+0.2 -0.2	+0.5 0	0 -0.5	+0.5 -0.5	H11	H9	H14	+0.5 0	MAX	+0.5 -0.5	+0.5 -0.5	
32	45	26	32.5	22	5	8	5.5	30	10	6.6	5.5	10	6.25	2	
40	55	28	38	25	5	8	5.5	35	12	6.6	5.5	12	8.5	2	
50	65	32	46.5	27	5	10	6.5	40	12	9	7.5	12	9.25	3	
63	75	40	56.5	32	5	10	6.5	45	16	9	7.5	15	9.25	3	
80	95	50	72	36	5	13	10	45	16	11	9	15	11.5	4	
100	115	60	89	41	5	13	10	55	20	11	9	20	13	4	
125	140	70 ^{-0.5} -1.2	110	50	7	16	10	60	25	13.5	10	25	15	5	
160	180	90 ^{-0.5} -1.2	140	55	7	20	10	65	30	18	13	25	20	5	
200	220	90 ^{-0.5} -1.2	175	60	7	20	11	75	30	18	13	25	22	-	
250	270	110 ^{-0.5} -1.2	220	70	11	25	11	90	40	22	16.5	40	25	-	ON DEMAND
320	350	120 ^{-0.5} -1.2	270	80	11	30	15	110	45	26	19.5	45	40	-	ON DEMAND

S12



DIAMETRO	PESO (KG)	CODICE BASE
DIAMETER	WEIGHT (KG)	BASE CODE
32	0,137	S12032
40	0,225	S12040
50	0,333	S12050
63	0,558	S12063
80	1,073	S12080
100	1,740	S12100
125	3,030	S12125
160	5,100	S12160
200	8,500	S12200
250		S12250
320		S12320

* DISPONIBILE ANCHE CON TRATTAMENTO DI ZINGATURA BIANCA / AVAILABLE ALSO WITH TREATMENT OF WHITE ZINC COATING

TRATTAMENTO: CATAFORESIS NERA *

TREATMENT: BLACK CATAPHORESIS *

MATERIALE: ACCIAIO

MATERIAL: STEEL