



DIAM.	TIPO	M	B	C	D	E	TOLERANZE				L	N	W1	W2	A°	NOTE
							+0.3	+0.3	+0.3	+0.3						
12-16	ISO	M6x1	36.5	11	3.5	18.5	6	8.5	14.5	13	1	12.5	7	5	6°	
20	ISO	M8x1.25	58	21	4	28.5	8	12.5	19	17	2	16	11	7	8°	
25-32	ISO	M10x1.25	74.5	23	6.5	36	14	22	32	30	2	22	19	12	8°	
32	DIN	M10x1.5	74.5	23	6.5	36	14	22	32	30	2	22	19	12	8°	
40	ISO	M12x1.25	75	24	6.5	36	14	22	32	30	2	22	19	12	8°	
40	DIN	M12x1.75	75	24	6.5	36	14	22	32	30	2	22	20	12	9°	
50-63	ISO	M16x1.5	103	30	10	53	22	32	45	41	2	30	30	20	6°	
80-100	ISO	M20x1.5	119	40	6.5	53	22	32	45	41	2	37	30	20	6°	
125	ISO	M27x2	147	54	10	71	-	59	60	55	2	40	32	24	8°	ON DEMAND
160-200	DIN	M36x2	241	72	15.5	125	-	56	80	75	2	40	50	36	8°	ON DEMAND

S45



DIAMETRO	PESO (KG)	CODICE BASE
DIAMETER	WEIGHT (KG)	BASE CODE
12-16	0,019	S45M06I
20	0,057	S45M08I
25-32	0,226	S45M10I
32	0,226	S45M10D
40	0,229	S45M12I
40	0,229	S45M12D
50-63	0,634	S45M16I
80-100	0,695	S45M20I
125	1,600	S45M27I
160-200	5,100	S45M36D